



ref.no.	size
29816	7/S
29817	8/M
29818	9/L
29825	10/XL

DE Kategorie III - Chemische und biologische Risiken - FR Catégorie III - Risques chimiques et biologiques - EN Category III - Chemical and biological risks - IT Categoria III - Rischi chimici e biologici - NL Kategorie III - Chemische en biologische risico's - PT Categoria III - Riscos químicos e biológicos - SV Kategori III - Kemiska och biologiska risker - FI Luokitus III - Kemialliset ja biologiset vaarat - DA Kategori III - Kemiske og biologiske risici - NO Kategori III - Kemiske og biologiske risikoer - PL Kategorie III - Zagrożenia chemiczne i biologiczne - HU III. kategória - Kémiai és biológiai kockázatok - SK Kategória III - Chemická a biologická rizika - CS Kategorie III - Chemická a biologická rizika - BG Категория III - Кемическа и биологическа опасност - RO Categoria III - Riscuri chimice și biologice - RU Категория III - Риск химической и биологической опасности

EN ISO 18889:2019 EN ISO 374-5:2016 EN 388:2016

EN ISO 18889:2019	EN ISO 374-5:2016	EN 388:2016
G2	VIRUS	A1:2018

DE PPE unterliegt dem Konformitätsbewertungsverfahren Modul D unter Überwachung der benannten Stelle: -FR L'ÉPI est soumis à la procédure d'évaluation de conformité Module D, sous surveillance de l'organisme notifié. - EN PPE is subject to the conformity assessment procedure Module D under surveillance of the notified body. - IT Il DPI è soggetto alla procedura di valutazione della conformità Modulo D sotto la sorveglianza dell'organismo accreditato. - NL PPE is onderhevig aan de procedure voor conformiteitsbeoordeling Modulo D, onder toezicht van de aangewezen instantie. - ES El EPI está sujeto al módulo D de evaluación de conformidad (módulo D bajo la supervisión de la autoridad notificada). - PT PPE sujeito ao procedimento de avaliação de conformidade, módulo D, sob a supervisão do organismo notificado. - SV Personlig skyddsutrustning omfattas av förfarandet för bedömning av överensstämmelse, modul D under övervakning av det ackrediterade organet. - FI Henkilösuojaimien (PPE) kelpoisuus yhdenmuotoisuuden moduulin D mukaisesti arvioidaan ja valvotaan valtuutetun organin toimesta. - DA Det personlige værnemiddel er omfattet af proceduren for overensstemmelsesvurdering modul D under overvågning af det bemyndigede organ. - NO FPU er ikke underlagt prosedyre for vurdering av samsvar modul D ved overvåking av teknisk kontrollorgan. - PL Wyposażenie ochronne objęte procedurą oceny zgodności wy modulu D pod nadzorem jednostki notyfikacyjnej. - HU A PPE (personál protection equipment - egyeni védőeszköz) a D modul megfelelőségi értékelés eljárásának hatálya alá tartozik a bejelentett szervezet által. - SK PPE podlieha postupu posudzovania zhody modulu D pod dohľadom notifikovaneho organu. - CS Osobní ochranné prostředky podléhají postupu posouzení shody modulu D pod dohledem notifikovaného orgánu. - SL Za OVO velja tudi D postopku ugotavljanja skladnosti pod nadzorstvom prijavljene agencije. - HR PPE je predmet postupka procjene skladnosti modula D pod nadzorom certifikacijskog tijela. - RU Категория III - Риск химической и биологической опасности - RO EPP este supus Modulului D al procedurii de evaluare a conformității sub supravegherea organismului notificat. - TR PPE, onaylanmış kurulum gözetimi altında uygunluk değerlendirme prosedürü Modül D'ye tabidir.

EN ISO 374-5:2016 Protection against bacteria and fungi; PPE: Protection against viruses: Pass Dexterity: Level 5

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		
99% Essigsäure (N):	86.9 %		

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Level	1	2	3	4	5	6
Breakthrough time (min)	>10	>30	>60	>120	>240	>480

EN ISO 374-5:2016 - Resistant to degradation against chemicals:

Methanol (A):	60.3 %	25% Ammonium Hydroxide (O):	-5.9 %
n-heptane (L):	-10.3 %	30% Waterstoffperoxid (P):	14.1 %
40% Sodium Hydroxide (K):	-4.9 %	37% Formaldehyd (T):	-8.4 %
96% Sulfaväure (L):	81.5 %	Toluol (F):	86.0 %
95% Nitric Acid (N):	97.0 %		



